

# 350kW DCFC

EVgo eXtend



Custom Branding Available

## KEY FEATURES

- ▶ DUAL CCS 1, DYNAMIC POWER SHARING, SIMULTANEOUS CHARGING
- ▶ EVgo CERTIFIED
- ▶ UL CERTIFIED: UL 2202, UL 2231-1, UL 2231-2
- ▶ ENERGY MANAGEMENT
- ▶ MEETS 150kW PER PORT NEVI FUNDING REQUIREMENTS
- ▶ ADA COMPLIANT
- ▶ CELLULAR COMMUNICATION TO EVgo BACKEND
- ▶ RFID, CREDIT CARD, ISO 15118 READY, AUTOCHARGE

## TECHNICAL SPECIFICATIONS

POWER LEVEL (kW)	350kW
EFFICIENCY	95%
SYSTEM	1 cabinet + 1 dispenser
INPUT VOLTAGE (AC)	480V
OUTPUT VOLTAGE MAX (DC)	950V
OUTPUT CURRENT MAX (DC)	540A
DIMENSIONS	Cabinet: 31.5" x 39.4" x 78.8", Dispenser: 19.1" x 26" x 78.7"
INGRESS PROTECTION	IP55, NEMA 3R
ENCLOSURE PROTECTION	IK 10